



GMC ENGINEERING EXCELLENCE IN A FIVE-PASSENGER CROSSOVER SUV.

The all-new five-passenger 2010 Terrain is the newest crossover from GMC that blends bold styling with premium features and outstanding fuel economy.* Highlights include an all-new 2.4L four-cylinder Direct Injection engine that offers an estimated highway fuel economy of 30 mpg.* There's also a standard Rear Vision Camera System and a MultiFlex® rear seat designed to provide a high level of passenger comfort and optimal cargo space.

Terrain is coming fall 2009, with front-wheel-drive and all-wheel-drive models offered in SLE and SLT trim levels. For more information, be sure to visit GMC.com/Terrain.



See your local GMC dealer for full details.

^{*}Terrain FWD 21 city/30 hwy. Based on GM preliminary development testing. Fuel economy development is not yet complete. Test results are not finalized. Official EPA estimates not yet available.





PACKAGED WITH PREMIUM FEATURES

The 2010 GMC Terrain will be available in four trim levels. All feature the 182-horsepower 2.4L Direct Injection Variable Valve Timing (VVT) engine mated to a 6-speed automatic transmission and Rear Vision Camera System.

Rear Vision Camera System is standard on all models.

SERIOUSLY WELL EQUIPPED

SLE-1

Includes 17-inch painted aluminum wheels, Rear Vision Camera System, fog lamps, heated outside rearview mirrors, six-speaker AM/FM/CD with integrated USB port and XM® Radio with three-month trial,* two-way power driver's seat and one year of OnStar®,† all standard.

SLE-2

Standard equipment includes a premium cloth interior, 8-way power driver's seat, leather-wrapped steering wheel, Bluetooth®†† connectivity for phone, automatic single-zone air conditioning and a premium Pioneer® 8-speaker audio system. Available features include the 3.0L V6 SIDI engine, 18- and 19-inch wheels, power sunroof, Dual Seatback DVD System and a Navigation System.§

SLT-1

Adds heated leather-appointed seating, 18-inch aluminum wheels and Remote Start as standard equipment, while offering options such as the 3.0L V6 SIDI engine, Power Programmable Liftgate, 19-inch chrome-clad aluminum wheels, power sunroof, Dual Seatback DVD System and a Navigation System.§

SLT-2

The most uplevel Terrain model features driver's side memory, Power Programmable Liftgate, power sunroof and a Chrome Exterior Appearance Package that includes chrome door handles, luggage rail inserts, grille, mirrors and body-color bumpers with chrome rear skid plates. Optional features mirror the SLT-1.

EXTERIOR COLORS

Carbon Black Metallic§

Gold Mist Metallic



Onyx Black



Cyber Gray Metallic



Atlantic Blue Metallic



Summit White



Mocha Steel Metallic



Merlot Jewel Metallic



Quicksilver Metallic





INTERIOR COLORS

- Jet Black
 - Base and Premium Cloth and Leather-Appointed
- Light Titanium
 - Base and Premium Cloth and Leather-Appointed
- Brownstone
 - Leather-Appointed

See your local GMC dealer for full details.

^{*}XM Radio requires a subscription, sold separately by XM/Sirius after the first 90 days. Not available in Alaska or Hawaii. For more information, visit gm.xmradio.com.

[†]Visit onstar.com for system limitations and details. †Go to gm.com/bluetooth to see which phones are compatible with each vehicle.

[§]Map coverage not available in Puerto Rico, the Virgin Islands and portions of Canada.

[§]Extra charge.

STANDARD CONTENT

SLE-1

- 17-inch painted aluminum wheels
- 2.4L I4 DI engine
- Acoustical Package
 - Laminated glass
 - Sound deadener
 - Triple door seals
- Ambient lighting (cupholder/center stack)
- Auto-dimming ISRV mirror with camera display
- Body-color door handles
- Body-color power-heated OSRVM (manual folding)
- Chrome moldings (beltline)
- Cloth interior
- Cruise control
- Daytime Running Lamps

- Deep-tinted glass
- Driver Information Center (DIC)
- Fog lamps with chrome bezel
- Four-wheel disc anti-lock brakes
- Projector Beam headlamps
- Six air bags*
 - Driver and front-passenger air bags
 - Driver and front-passenger thorax air bags
 - Head-curtain side air bags (first and second row)
- Illuminated driver and passenger vanity mirrors
- MultiFlex rear seat (with 60/40 split)
- OnStar®** with one-year of Safe & Sound plan
- Power door locks

- Power windows
- Rear Vision Camera System
- Rear spoiler
- Remote Keyless Entry (extended range)
- Single-zone air conditioning
- Six-speaker audio with CD/MP3/USB and auxiliary jack
- Six-speed automatic transmission
- StabiliTrak® with Traction Control
- Tilt and telescoping steering wheel
- Tire Pressure Monitoring System
- Two-way power driver's seat (power lumbar and height/manual fore/aft)
- Two-way manual passenger's seat
- Comfort grip steering wheel
- XM®† Radio with three-month trial

SLE-2

Includes all SLE-1 content with the following additions/replacements:

- Ambient lighting in overhead IP
- Bluetooth®†† for phone
- Eight-way power driver's seat (power lumbar/manual recline)
- Leather-wrapped steering wheel with audio controls
- Pioneer® premium eight-speaker audio system
- Roof rails (Charcoal)
- Single-zone automatic air conditioning

SLT-1

Includes all SLE-2 content with the following additions/replacements:

- 18-inch machined aluminum wheels
- Leather-appointed seating with heated front seats
- Remote Start

SLT-2

Includes all SLT-1 content with the following additions/replacements:

- Ambient lighting in door storage/handles. footwells and cupholders
- Chrome Exterior Appearance Package
- Memory settings (driver's seat and mirrors)
- Power Programmable Liftgate
- Power sunroof
- Rear Park Assist

OPTIONAL EQUIPMENT

SLE-1	SLE-2	SLT-1	SLT-2
	1,500-lb. Trailering Package§	1,500-lb. Trailering Package§	1,500-lb. Trailering Package§
	3,500-lb. Trailering Package§	3,500-lb. Trailering Package§	3,500-lb. Trailering Package§
	Sunroof	Sunroof	
	3.0L V6 DI engine (includes dual chrome exhaust)	3.0L V6 DI engine (includes dual chrome exhaust)	3.0L V6 DI engine (includes dual chrome exhaust)
	18-inch bright machined aluminum wheels		
	19-inch chrome-clad aluminum wheels (requires V6 engine)	19-inch chrome-clad aluminum wheels (requires V6 engine)	19-inch chrome-clad aluminum wheels (requires V6 engine)
	Dual Seatback DVD System	Dual Seatback DVD System	Dual Seatback DVD System
	Navigation System§§	Navigation System§§	Navigation System§§
		Power Programmable Liftgate	

OPTION PACKAGES

SLE-1	SLE-2	SLT-1	SLT-2
	Cargo Package	Cargo Package	Cargo Package
	Convenience Package (Remote Start and heated cloth seats)		

^{*}Always use safety belts and the correct child restraints for your child's age and size. Even in vehicles equipped with air bags and the Passenger Sensing System, children are safer when properly secured in a rear seat in an appropriate infant, child or booster seat. Never place a rear-facing infant restraint in the front seat of any vehicle equipped with an active frontal air bag. See the vehicle's Owner's Manual and child safety seat instructions for more safety information. Head-curtain side air bags are designed to help reduce the risk of head and neck injuries to front and rear seat occupants on the near side of certain side-impact collisions.

^{**}OnStar services require vehicle electrical system (including battery), wireless service, and GPS satellite signals to be available and operating for features to function properly. OnStar acts as a link to existing emergency service providers. OnStar Vehicle Diagnostics available on most 2004 model year and newer GM vehicles. Diagnostic capability varies by model. Visit onstar.com for system limitations and details.

†XM Radio requires a subscription, sold separately after the first 90 days. Not available in Alaska or Hawaii. For more information, visit gm.xmradio.com.

^{&#}x27;'Go to gm.com/bluetooth to see which phones are compatible with each vehicle.

'Maximum trailer ratings are calculated assuming standard equipped vehicle, driver and required trailering equipment. The weight of optional equipment, passengers and cargo will reduce the maximum trailer weight the vehicle can tow. 10% to 15% of the trailer weight is the recommended trailer tongue load.

⁵⁵ Map coverage not available in Puerto Rico, the Virgin Islands and portions of Canada.



	ONS	
Overall Length (in./mm)	185.3/4705	
Overall Width (in./mm)	72.8/1850	
Overall Height (in./mm)	66.3/1684	
Wheelbase (in./mm)	112.5/2857	
Front Overhang (in./mm)	35.7/908	
Rear Overhang (in./mm)	37.0/941	
NTERIOR DIMENSI	ONS	
Seating Capacity (front/rear)	2/3	
Headroom (in./mm)	front: 39.8/1012 rear: 39.2/995	
Legroom (in./mm)	front: 41.2/1046 rear: 37.2/946	
Shoulder Room (in./mm)	front: 55.7/1416 rear: 55.3/1404	
Hip Room (in./mm)	front: 55.1/1399 rear: 51.3/1304	
EPA Passenger Volume (cu. ft./L)	99.6/2820	
EPA Interior Volume (cu. ft./L)	127.2/3602	
CAPACITIES		
Trailer Towing* Maximum (lb./kg)	3.0L V6 = 3500/1588 2.4L I4 = 1500/680	
Fuel Tank (approx. gal.)	18.8-gal. w/2.4L I4 (FWD and AWD); 20.9-gal. w/3.0L V6 models (FWD and AWD)	
2.4L DOHC DI VVT I	4	
Туре	2.4L DOHC I4; four valves per cylinder	
Ignition System	Spark ignition direct injection (SIDI)	
Output (hp @ rpm)	182 @ 6700	
Torque (lbft. @ rpm)	174 @ 4800	
Recommended Fuel	Regular unleaded	
Estimated Fuel Economy [†] (city/hwy)	FWD = 21/30 AWD = 20/27	
B.OL DOHC DI VVT V	16	
Туре	3.0L DOHC V6; four valves per cylinde	
Ignition System	Spark ignition direct injection (SIDI)	
Output (hp @ rpm)	264 @ 6950	
Torque (lbft. @ rpm)	222 @ 5100	
Recommended Fuel	Regular unleaded	
Estimated Fuel Economy	FWD = 18/25	

6T45 AUTOMATIC	TRANSMISSION
Туре	Six-speed transverse, electronically controlled, automatic overdrive transmission
Application	Standard w/2.4L DI VVT I4
6T70 AUTOMATIC	TRANSMISSION
Туре	Six-speed transverse, electronically controlled, automatic overdrive transmission
Application	Mated w/3.0L DI VVT V6; Optional on SLE-2 and SLT
CHASSIS/SUSPEN	SION
Front	Independent, strut-type, specifically tuned coil springs, direct-acting stabilizer bar (hollow); hydraulic ride bushings
Rear	Independent, trailing arm with three lateral locating links, indirect- acting stabilizer bar (hollow), specifically tuned coil springs; hydraulic link bushings
Traction Control	All-speed, using engine torque reduction and brake intervention
Steering Type	Specifically calibrated hydraulic- power-assisted rack-and-pinion for V6 models; specifically calibrated rack- mounted electric power steering for 4-cylinder models
Steering Wheel Turns, Lock-to-lock	REPS = 3.46 HPS = 2.9 w/18-inch wheels; 2.8 w/19-inch wheels
Turning Circle, Curb-to-Curb (ft./m)	w/17-inch wheels/tires = 40.0/12.2 w/18-inch wheels/tires = 40.0/12.2 w/19-inch wheels/tires = 42.6/13.0
Steering Ratio	2.4L I4 VVT DI w/REPS = 18.1:1 3.0L V6 VVT DI w/HPS = 17.4:1
BRAKES	
Туре	Four-wheel power disc w/ABS (w/ESC); vented front and rear rotors, cast iron calipers, front and rear
Brake Rotor Diameter – front (in./mm)	321 x 30 mm vented; single piston 60 mm cast iron caliper
Brake Rotor Diameter – rear (in./mm)	303 x 20 mm vented; single piston 40 mm cast iron caliper
WHEELS/TIRES	
Wheel Size and Type	17-inch painted aluminum (w/2.4L I4) 18-inch bright machined aluminum 19-inch chrome-clad aluminum (opt. on V6 models)
Tires	17-inch P225/65R17-100S BW TL ALS 18-inch P235/55R18-99T BW TL AL2 19-inch P235/55R19-101H BW TL AL3
Preliminary information displayed. Su	ubject to change.

^{*}Maximum trailer ratings are calculated assuming standard equipped vehicle, driver and required trailering equipment. The weight of optional equipment, passengers and cargo will reduce the maximum trailer weight the vehicle can tow. 10% to 15% of the trailer weight is the recommended trailer tongue load.

*Based on GM preliminary development testing. Fuel economy development is not yet complete. Test results are not finalized. Official EPA estimates not yet available.