

HUMMER H1







4-DOOR WAGON

4-DOOR OPEN TOP

COMPONENTS & FEATURES

ENGINE: V8, 6.5L Turbocharged diesel, electronically-controlled HORSEPOWER (SAE hp): (est.) 195 @ 3400 rpm TORQUE (lb.-ft/Nm): (est.) 430 lb-ft @ 1800 rpm

TRANSMISSION: 4L80-E 4-speed automatic

POWERTRAIN: Full-time 4WD with TorqTrac® 4 (TT4) traction system

TRANSFER CASE: New Venture Gear model 242

GEARED HUBS: Gear ratio of 1.92:1

DIFFERENTIAL: Zexel Torsen® III torque biasing differential

STEERING: Power assisted

BRAKES: Hydroboost 4-wheel in-board mounted Meritor-WABCO ABS

power disc brakes

SUSPENSION: Independent double A frame with open-end coil springs and

hydraulic shock absorbers

LENGTH: 184.5 in. (NOTE 1)

FRAME: Steel box section with five cross members

SPECIFICATIONS & PERFORMANCE DATA

HEIGHT:

4-DOOR OPEN TOP: 77 in. 4-DOOR WAGON: 75 in.

WIDTH (EXCLUDING MIRRORS): 86.5 in.

WHEELBASE: 130 in.
TRACK WIDTH: 71.6 in.
GROUND CLEARANCE: 16 in.
APPROACH ANGLE: 72°
DEPARTURE ANGLE: 37.5°
MAXIMUM TOWED LOAD: (NOTE 2)
4-DOOR OPEN TOP: 7,986 lb.

4-DOOR WAGON: 7.646 lb.

RUNFLAT CAPABILITY: 20 miles @ 30 mph (NOTE 3)

TURNING RADIUS: 26.5 ft.

FUEL CAPACITY: 25 gallon tank plus 17 gallon auxiliary tank

For more information check out www.HUMMER.com or call us at 1 800 REAL 4WD.

STANDARD EXTERIOR EQUIPMENT

6061 T6 hardened aircraft aluminum body

Composite hood

Heavy duty steel bumper towing shackles

3/16 in. rocker panel protection constructed from T6 aluminum

Brush guard

Driveline protection

Trailer towing unit with wiring harness

Heated power mirrors

STANDARD INTERIOR EQUIPMENT

Cloud Gray cloth interior

Remote keyless entry

Power windows (express down for driver)

Monsoon® audio system with 6-disc CD player/changer and cassette

Air conditioning with auxiliary rear unit

Air inflation line with quick connects

E-Z Kool® glass (windshield, passenger, driver windows)

Heated windshield

CTIS controls and in-dash tire pressure gauges

OPTIONAL EQUIPMENT

 $17\ \text{in.}\ 2\text{-piece}$ forged aluminum wheels with dual beadlocks and Runflats featuring a fully concealed air delivery system to support CTIS

 $37 \times 12.5R-17$ load range "E" Goodyear Wrangler MT/R tire with DuraWall puncture resistance technology

12,000 lb. winch

WHEELS & TIRES

17 in. 1-piece cast aluminum wheels

 $37\ x\ 12.5 R\text{-}17$ load range "E" Goodyear Wrangler GSA radial

Central Tire Inflation System (CTIS) with on-board air compressor

Tire bead retaining system

Runflat tire system (NOTE 3)

Concealed air delivery system

EXTERIOR COLORS







Competition Yellow



Ocean Blue Metallic



Firehouse Red



Metallic Pewter



Silver Metallic



Woodland Green

